

Accessing External Databases

From ILE RPG (with help from Java)



Presented by

Scott Klement

<http://www.scottklement.com>

© 2008, Scott Klement

“There are 10 types of people in the world.
Those who understand binary, and those who don't.”

Objectives Of This Session



- Understand why you should use JDBC drivers from RPG.
- Understand how to install the JDBC drivers
- Understand how to use the JDBC drivers from RPG
- Learn where to find more information

Note: JDBC provides SQL access to a database. If you don't have at least a basic understanding of SQL, this session might be hard to follow.


A Solution to a Problem



- Virtually all businesses today use more than one computer platform. Unlike 20 years ago, no company is "AS/400 only".
- A Windows programmer can access any database on any platform
 - Database manufacturer provides a "driver"
 - Install driver into ODBC framework to enable programs to access the database.
- Few database manufacturers make drivers for i5/OS
 - Market is too small?
 - RPG programmers haven't expressed enough interest?
- Manufacturers make drivers for Java – and Java runs on any platform!
- RPG can call Java methods directly on V5R1 and later.
 - So RPG can use Java's drivers – enabling access to just about any database on the market!

3

Component Overview



4

JDBC Drivers Provide



- JDBC = Java Data Base Connectivity
- Provide a means for Java (and RPG!) code to access a database
- Access is done through SQL statements
- SQL statements can do most anything:
 - Read data bases (SELECT statement)
 - Update (UPDATE statement)
 - Add new records (INSERT statement)
 - Create new databases, tables, indexes, views (CREATE statements)
 - Etc.
- This is done through calls to the JDBC drivers (not via RPG's normal "embedded SQL preprocessor").
- Scott has provided JDBCR4, an RPG wrapper to simplify calling JDBC.

5

Drivers You Can Use



- Driver must be "type 4", which means it's pure Java
 - Other drivers work by calling a Windows DLL, which will not work.
 - Type 4 is pure Java – so will run on all platforms.

Microsoft SQL Server's driver is Type 4 with one caveat

- sqljdbc_auth.dll is required to use "Windows Authentication".
- From i5/OS, you can't use windows authentication, and must use SQL authentication.

Oracle refers to their Type 4 driver as a "thin" driver.

MySQL refers to theirs as "Connector/J".

Note: Although this presentation gives examples for MS SQL Server, Oracle, MySQL and IBM DB2, it should work with any database, as long as you can find a type 4 driver and figure out the correct connection string.

6

Install Into Your System i



- JDBC type 4 drivers are Java classes. They are almost always packaged in a JAR file.
 - The vendor often puts the JAR file inside a ZIP or EXE file along with other stuff such as documentation, the license agreement, etc.
1. Download/Unzip/Install the vendor's package on your PC.
 2. Upload the JAR file (or files) to the IFS on your System i.
 - MySQL: `mysql-connector-java-3.1.12-bin.jar`
 - Oracle: `ojdbc14.jar`
 - SQL Server: `sqljdbc.jar`
 - i5/OS DB2: `jt400.jar`
 - IBM DB2: `db2jcc.jar`
 3. Add the JAR file (using the full IFS path name) to your CLASSPATH.
 4. When RPG calls Java, the Java database manager will use the CLASSPATH to find the driver.

7

Example of Installing JDBC driver



- Create an IFS folder to store my JDBC drivers.

```
CRTDIR DIR('/java') DTAAUT(*RX) OBJAUT(*NONE)
CRTDIR DIR('/java/jdbc') DTAAUT(*RX) OBJAUT(*NONE)
```
- Download the SQL server driver from Microsoft (download links are at the end of the presentation)
- Run (double-click) the EXE file to unzip it. Tell it to unzip to the C:\JDBC folder.
- Use FTP in BINARY mode to copy the sqljdbc.jar file from the `c:\JDBC\SQLJDBC_1.2\ENU` folder to the `/java/jdbc` folder in my IFS.
- Set my CLASSPATH as follows:

```
ADDENVVAR ENVVAR(CLASSPATH) VALUE('/java/jdbc/sqljdbc.jar')
```

- **CLASSPATH must be set before JVM is loaded.**
- **Do it after a fresh sign off/on.**

8

Needed Information



Information You'll Need:

- Fully-qualified Java class name of driver.

SQL Server: com.microsoft.sqlserver.jdbc.SQLServerDriver
Oracle: oracle.jdbc.OracleDriver
MySQL: com.mysql.jdbc.Driver
i5/OS DB2: com.ibm.as400.access.AS400JDBCdriver
Other DB2: com.ibm.db2.jcc.DB2Driver

- Connection String

SQL Server: jdbc:sqlserver://myserver.example.com:1433
Oracle: jdbc:oracle:thin:@myserver.example.com:1521:myDataBase
MySQL: jdbc:mysql://myserver.example.com/myDataBase
i5/OS DB2: jdbc:as400://myserver.example.com
Other DB2: jdbc:db2://myserver.example.com:50000/myDataBase

- Any needed properties

- Usually a username & password.
- Sometimes other attributes (*SYS vs *SQL, How errors are reported, etc.)

9

Getting Needed Info for Other Drivers



If you need to use a different JDBC driver than the ones I've listed here, how do you know what the class name and connection string should be?

The easiest solution is to look at sample Java code that uses the driver. This'll be included in the driver's documentation, or else by searching the web.

Class name can be found in a statement like one of these:

```
Class.forName("com.ibm.as400.access.AS400JDBCdriver")  
-- OR --  
DriverManager.registerDriver(new com.ibm.as400.access.AS400JDBCdriver());
```

The connection string will be in a DriverManager.getConnection call:

```
conn = DriverManager.getConnection("jdbc:db2://example.com:50000/phonedb" . . .
```

10

Introducing JDBCRC4



- JDBCRC4 is an RPG service program that Scott wrote to simplify the task of calling JDBC from RPG.
- It was originally written for articles about JDBC in the System iNetwork Programming Tips newsletter.
- Links to the articles where you can download the code (for free) are provided at the end of this presentation.
- The RPG sample code in this article will use this service program.
- You could certainly call the Java methods without using this service program (*but why??*)
 - Write your own prototypes
 - Write your own routines to convert between Java & RPG data types.

11

RPG Code to Connect



JDBC_Connect() connects to a database w/userid & password.

- *First parameter is the Java class name of the JDBC driver to load*
- *Second parameter is the connection string.*
- *Last two parameters are the user name & password.*

```
/copy JDBC_H
D user          s          50a
D passwd       s          50a
D conn         s          like(Connection)
.
.
user = 'klemscot';
passwd = 'bigboy';

conn = JDBC_Connect( 'com.mysql.jdbc.Driver'
                    : 'jdbc:mysql://myserver.example.com/myDataBase'
                    : %trim(user)
                    : %trim(passwd) );

if (conn = *NULL);
    errorMsg = 'Unable to connect to MYSQL database!';
    // show message to user.
endif;
```

To connect to a different type of database, provide the correct class and connection string.

12

Fixed Format RPG



If you like, you can also use fixed-format RPG – use EVAL or CALLP statements.

```
D user          s          50a
D passwd       s          50a
D conn         s              like(Connection)
.
.
C              eval        user = 'klemscot'
C              eval        passwd = 'bigboy'

C              eval        conn = JDBC_Connect(
c              'com.mysql.jdbc.Driver'
c              : 'jdbc:mysql://myserver.example'
c              + '.com/myDataBase'
c              : %trim(user): %trim(passwd))
c              if          conn = *null
c              eval        errorMsg = 'Connect failed'
C***          show message to user
c              endif
```

RPG Connect w/Properties



```
/copy JDBC_H
D user          s          50a
D passwd       s          50a
D conn         s              like(Connection)
D prop         s              like(Properties)

user = 'klemscot';
passwd = 'bigboy';

prop = JDBC_Properties();
JDBC_setProp(prop: 'user'          : %trim(userid) );
JDBC_setProp(prop: 'password'      : %trim(passwd));
JDBC_setProp(prop: 'connectTimeout': '60'          );

conn = JDBC_ConnProp( 'com.mysql.jdbc.Driver'
                    : 'jdbc:mysql://myserver.example.com/myDataBase'
                    : prop);

if (conn = *NULL);
    errorMsg = 'Unable to connect to MYSQL database!';
    // show message to user.
endif;

JDBC_freeProp(prop);
```

Another Properties Example



```
D conn          s          like(Connection)
D prop          s          like(Properties)

/free

prop = JDBC_Properties();
JDBC_setProp(prop: 'user'      : 'klemscot' );
JDBC_setProp(prop: 'password': 'bigboy'   );
JDBC_setProp(prop: 'prompt'   : 'false'    );
JDBC_setProp(prop: 'errors'   : 'full'     );
JDBC_setProp(prop: 'naming'   : 'system'   );
JDBC_setProp(prop: 'libraries': '*LIBL,ISNMAG');

conn = JDBC_ConnProp( 'com.ibm.as400.access.AS400JDBCdriver'
                    : 'jdbc:as400://localhost'
                    : prop );
JDBC_freeProp(prop);

if (conn = *NULL);
    return;
endif;
```

15

Types of Java SQL Statements



- Immediate Statements
SQL string is interpreted by database, and then run immediately.
- Prepared Statements
SQL string is "compiled" by database.
Statement can then be run multiple times without re-compiling.
You can fill-in placeholders with values before statement is run.
- Callable statements
Very much like a prepared statement, except that it calls a stored procedure.
- *types of statements used with the above methods* ----
- "Query" Statements
Statements that return a "Result Set" (very much like a cursor, except it contains meta-information about columns in the result set.)
- "Update" Statements
Statements that do not return a result set. Name is not quite accurate, you can use this for anything that doesn't return a result set, including DDL, INSERT, UPDATE, etc.
- "Call" Statements

16

Routines For Immediate Statements



- JDBC_ExecUpd(connection : sql statement string)
Run an "update" statement (one that does not return a result set).
Wrapper for the Java executeUpdate() method.

Returns the number of rows affected
or 0 for statements that don't affect rows (such as "create table")
or -1 if an error occurs.

- JDBC_ExecQry(connection : sql statement string)
Run a "query" statement (one that returns a result set).
Wrapper for the Java executeQuery() method.

Returns a ResultSet object. (like a cursor – used to retrieve results of statement)
Or *NULL if an error occurs.

17

Immediate "Update" Example



```
. . . Make Connection Here . . .

rc = JDBC_ExecUpd( conn : 'Create Table Item_Information'
+ '('
+ ' ItemNo      Dec(5,0) Not Null, '
+ ' Count       Int Not Null, '
+ ' LastChg     Timestamp '
+ '           Default CURRENT_TIMESTAMP, '
+ ' LastSold    Date Default Null, '
+ ' TimeTest    Time Default Null, '
+ ' Price       Dec(7,2) Not Null, '
+ ' Description VarChar(25) not Null '
+ ')' );

if (rc < 0);
    ErrMsg = 'Unable to CREATE table';
    // show error message to user
endif;
```

NOTE: SQL Statements should be in the syntax of the target database. This lets you take advantage of any extensions they have to the SQL standard. JDBC does have a tool called "escaping" that can help make your statements database-neutral. See links at the end of this talk for more about escaping.

18

Working With a Result Set



- **JDBC_ExecQry(connection : sql statement string)**
Run a "query" statement (one that returns a result set).
Wrapper for the Java executeQuery() method.
Returns a result set, or *NULL upon error.

--- when working with result sets, use the following ---

JDBC_nextRow(ResultSet)

- advances to the next available row in a result set.
- Returns *ON if successful, *OFF if you've reached the end of the result set.

JDBC_getCol(ResultSet : ColNo)

- Returns the value of a column in the result set.
- Column is identified by ordinal number. (first col returned is number 1, second is number 2, etc.)

JDBC_getColByName(ResultSet : ColumnName)

- Returns the value of a column in the result set using the column name.

JDBC_freeResult(ResultSet)

- Closes the ResultSet (like closing a cursor in embedded SQL)
- Frees up the memory used by the result set.

19

Immediate "Query" Example



```
D ResSet          s          like(ResultSet)

. . . Connect as before . . .
ResSet = JDBC_ExecQry( conn : 'Select Department, +
                             Employee_No, +
                             Employee_Name +
                             from Employee_Master +
                             order by Department' );

if (ResSet = *null);
  ErrMsg = 'Error running SELECT statement';
  // show error message to user
endif;

dow JDBC_nextRow(ResSet);
  Dept = JDBC_getCol(ResSet: 1);
  EmpNo = %int(JDBC_getCol(ResSet: 2));
  Name = JDBC_getCol(ResSet: 3);

. . . Print Dept, EmpNo, Name or whatever here . . .

enddo;

JDBC_freeResult(ResSet);
```

Java will convert columns to character, as needed. You can use RPG to convert it back, as needed.

20

Prepared Statements



- JDBC_PrepStmt(connection : SQL statement string)
 - Returns a PreparedStatement Java object for the given SQL statement.
 - It "prepares" the SQL statement.
 - I like to think of this as "compiling" the statement, so that the code in the statement can be run again and again quickly.
 - Placeholders (called "parameter markers") can represent variable values, letting you re-run a statement without having to prepare a new statement.
 - The "parameter markers" also help you avoid "SQL Injection Attacks"

JDBC_ExecPrepUpd(PreparedStatement)

- Runs a prepared statement that does not return a result set.

JDBC_ExecPrepQry(PreparedStatement)

- Runs a prepared statement that returns a result set

JDBC_FreePrepStmt(PreparedStatement)

- Frees up the memory used by a Prepared Statement

21

Prepared Statement Query



```
D Stmt          s          like(PreparedStatement)
D ResSet        s          like(ResultSet)
. . . Connect as before . . .

Stmt = JDBC_PrepStmt( conn : 'Select Department, +
                             Employee_No, +
                             Employee_Name +
                             from Employee_Master +
                             order by Department' );

if ( stmt = *null );
  // error occurred
endif

ResSet = JDBC_ExecPrepQry( Stmt );
if (ResSet = *null);
  // error occurred.
endif;

. . . Read the Result Set The Same Way You Did with
      an immediate statement . . .

JDBC_freeResult( ResSet );
JDBC_freePrepStmt( stmt );
```

22

Parameter Markers



You place a ? where you want data inserted. Then you number the markers from left to right, and set them by number by calling the following routines:

- JDBC_setString(stmt : parameter number : 'String Value');
- JDBC_setInt(stmt : parameter number : integer value);
- JDBC_setDouble(stmt : parameter number : floating point value);
- JDBC_setDecimal(stmt : parameter number : decimal number);
- JDBC_setDate(stmt : parameter number : date field);
- JDBC_setTime(stmt : parameter number : time field);
- JDBC_setTimestamp(stmt : parameter number : timestamp field);

23

Parameter Marker Example



```
Stmt = JDBC_PrepStmt( conn : 'Select Department, +
                             Employee_Name +
                             from Employee_Master +
                             where Employee_No=?' );

if ( stmt = *null );
    // error occurred
endif

EmpNo = 1234;
JDBC_SetInt( stmt: 1: EmpNo );

ResSet = JDBC_ExecPrepQry( Stmt );
if (ResSet = *null);
    // error occurred.
endif;

. . . Read the Result Set The Same Way You Did with
       an immediate statement . . .

JDBC_freeResult( ResSet );
JDBC_freePrepStmt( stmt );
```

24

Prepared Statement Insert



```
Stmt = JDBC_PrepStmt( conn : 'Insert Into Employee_Master +
                        (Employee_No, +
                        Employee_Name, +
                        Department ) +
                        Values (?, ?, ?)' );

if ( stmt = *null );
  // error occurred
endif

JDBC_setInt    ( stmt: 1: 4321 );
JDBC_setString( stmt: 2: 'Klement, Scott C. ');
JDBC_setString( stmt: 3: 'IT' );
if JDBC_execPrepUpd( stmt ) < 0;
  // Insert Failed.
endif;

EmpNo = 4322;
Name  = 'John Q. Public';
Dept  = 'AP';
JDBC_setInt( stmt: 1: EmpNo );
JDBC_setString( stmt: 2: Name );
JDBC_setString( stmt: 3: Dept );
JDBC_execPrepUpd( stmt );
```

You can use literals, constants or values

25

Wrapped In a Procedure



```
WriteRec( stmt: 1234: 'Alex Aguilera': 'SHP' );
WriteRec( stmt: 1002: 'Jerry Berry': 'PKG' );
WriteRec( stmt: 2001: 'Paul Smith': 'SALES' );
JDBC_FreePrepStmt( stmt );
```

```
P WriteRec      B
D WriteRec      PI              1N
D Stmt          like(PreparedStatement)
D EmpNo         5s 0 value
D Name          30a const
D Dept          5a const
/free
JDBC_setInt    ( stmt: 1: EmpNo );
JDBC_setString( stmt: 2: Name );
JDBC_SetString( stmt: 3: Dept );

if JDBC_ExecPrepUpd( stmt ) < 0;
  return *OFF;
else;
  return *ON;
endif;
/end-free
P              E
```

I often like to wrap my inserts or updates into subprocedures so I can call them in a manner that's more like RPG's native I/O.

26

Running Callable Statements



Callable statements are very much like Prepared Statements that return result sets. The only real difference is that they call routines instead of accessing databases.

Like all SQL executed through JDBC, the syntax of the SQL statements varies from one platform to the next.

JDBC_PrepCall(Connection : Call Statement String)

Prepares a callable statement.

JDBC_RegisterOutParameter(CallableStatement: Parm No: DataType)

Notifies JDBC that one of the parameters will be used to return data from the stored procedure. By default, all parameters are input only.

JDBC_ExecCall(CallableStatement)

Execute a callable statement

JDBC_FreeCallStmt(CallableStatement)

Free up the memory used by a callable statement.

27

Results from Callable Statements



Stored procedures can return an update count (like an "update" statement) or they can return one or more result sets. The return value from JDBC_ExecCall() will be *ON if a result set is returned, or *OFF otherwise.

JDBC_getUpdateCount(CallableStatement)

When no result set is returned, this gives you a count of the number of affected rows (ala executeUpdate).

JDBC_getResultSet(CallableStatement)

When one (or more) result sets are returned, this gives you the result set. It returns a ResultSet object (ala executeQuery).

JDBC_getMoreResults(CallableStatement)

Advances to the next result set if more than one were returned. Returns *ON if another result set is found, *OFF otherwise – also closes ResultSet.

JDBC_getString(), JDBC_getInt(), JDBC_getShort(), JDBC_getBoolean()

Get the values of output parameters passed from the stored procedure.

28

Stored Procedure Example



```
D stmt          s          like(CallableStatement)
D rs            s          like(ResultSet)
D IsResultSet   s          in

      stmt = JDBC_PrepCall( conn
                          : 'call order_new(012001)' );

      IsResultSet = JDBC_execCall( stmt );

      dow IsResultSet;
        rs = JDBC_getResultSet( stmt );

        dow JDBC_nextRow(rs);
          field1 = JDBC_getCol(rs: 1);
          field2 = JDBC_getColByName(rs: 'SecondField');
          . . . etc . . .
        enddo;

      IsResultSet = JDBC_getMoreResults( stmt );
    enddo;

      JDBC_FreeCallStmt(stmt);
      JDBC_Close(conn);
```

29

Result Set Meta-Data



This neat feature of JDBC lets you get information about the result set that was returned from an SQL statement, such as:

- *Number of columns*
- *Name, Data Type, Size, Decimal Positions of each column*

Useful for writing "dynamic" applications where the data that's returned might not be the same each time.

- Generic report program (user feeds an SQL statement, and you print a report.)
- Stored procedures that can return different result sets

TIP: WORKS GREAT FOR TESTING THE EXTERNAL STORED PROCEDURES YOU'VE WRITTEN IN RPG!

Meta-Data Routines



JDBC_getMetaData(ResultSet)

Retrieve the meta data from a result set. This meta data object is used with the following routines.

JDBC_getColCount(MetaData)

Returns the number of columns in the result set.

JDBC_getColName(MetaData : Col No)

Returns the name of one of the columns in the result set.

JDBC_getColDspSize(MetaData: Col No)

Returns the size of a column (intended for display) in the result set.

JDBC_getColTypeName(MetaData: Col No)

Returns the data type of a column in the result set.

31

Meta-Data Example (1 of 4)



```
H DFTACTGRP(*NO) BNDDIR('JDBC')

/copy jdbc_h

D conn          s          like(Connection)
D prop          s          like(Properties)
D stmt          s          like(CallableStatement)
D rs            s          like(ResultSet)
D rsmd          s          like(ResultSetMetaData)
D IsResultSet   s          1n
D x             s          10i 0
D msg          s          52a

/free

prop = JDBC_Properties();
JDBC_setProp(prop: 'user'      : 'klemscot' );
JDBC_setProp(prop: 'password': 'bigboy'   );
JDBC_setProp(prop: 'prompt'  : 'false'    );
JDBC_setProp(prop: 'errors'  : 'full'     );
JDBC_setProp(prop: 'naming'  : 'system'   );
JDBC_setProp(prop: 'libraries': 'FILES,QGPL,QTEMP,ISNMAG');
```

32

Meta-Data Example (2 of 4)



```
conn = JDBC_ConnProp( 'com.ibm.as400.access.AS400JDBCdriver'
                    : 'jdbc:as400://localhost'
                    : prop );

JDBC_freeProp(prop);

if (conn = *NULL);
    // error connecting...
endif;

stmt = JDBC_PrepCall( conn
                    : 'call order_new(012001)' );

IsResultSet = JDBC_execCall( stmt );
```

NOTE: If you replace
JDBC_PrepCall with
JDBC_PrepStmt, you could
use the same logic to run a
regular SQL statement –
such as a SELECT.

33

Meta-Data Example (3 of 4)



```
dow IsResultSet;
  rs = JDBC_getResultSet( stmt );
  rsmd = JDBC_getMetaData(rs);

  dow JDBC_nextRow(rs);
    for x = 1 to JDBC_getColCount(rsmd);
      msg = JDBC_getColName(rsmd: x)
          + '='
          + JDBC_getCol(rs: x);
      dsply msg;
    endfor;
  enddo;

  IsResultSet = JDBC_getMoreResults( stmt );
enddo;

JDBC_FreeCallStmt(stmt);
JDBC_Close(conn);
*inlr = *on;

/end-free
```

34

Meta-Data Example (4 of 4)



This sample program just outputs the column names & their values with DSPLY, so they'll appear in my job log, as follows:

```
DSPLY ORDERNO=A0000015
DSPLY CUSTNO=12001
DSPLY SCAC=UPSN
DSPLY SHIPNAME=Scott Klement
DSPLY SHIPADDR1=System iNEWS Magazine
DSPLY SHIPADDR2=321 Sesame St.
DSPLY SHIPADDR3=Franklin, WI 53132
DSPLY BILLNAME=Wayne Madden
DSPLY BILLADDR1=Penton Technology Media
DSPLY BILLADDR2=123 29th St.
DSPLY BILLADDR3=Loveland, CO.
DSPLY SHIPDATE=2008-03-01
DSPLY MSGID=
DSPLY MSG=
```

35

Miscellaneous



Support for Nulls

- To support null fields in databases, the JDBC_getCol() and JDBC_setXXX procedures have an optional parameter of type "named indicator".
- If you pass this parameter when reading a column, it'll be turned on if the field is set to null in the database.
- If you pass this parameter when setting the value for a column, then the field will be marked as null if the indicator is on, not-null, otherwise.

Commitment Control

- In addition to the other procedures mentioned, JDBC4 has procedures for commitment control.
- **JDBC_Commit()** commits transactions to disk.
- **JDBC_Rollback()** rolls the values back.

36

Links to JDBC Drivers



Oracle Driver

http://www.oracle.com/technology/software/tech/java/sqlj_jdbc/index.html

Oracle JDBC FAQ

http://www.oracle.com/technology/tech/java/sqlj_jdbc/htdocs/jdbc_faq.htm

SQL Server JDBC Driver (some folks have had problems with version 1.2, if you have problems, try downloading the version 1.1 driver):

<http://msdn.microsoft.com/en-us/data/aa937724.aspx>

MySQL Connector/J Driver:

<http://www.mysql.com/products/connector/j/>

IBM DB2 UDB Driver (Windows or Linux DB2)

<http://www.ibm.com/db2>

IBM DB2 UDB Driver (for i5/OS)

<http://publib.boulder.ibm.com/infocenter/iserics/v5r4/topic/rzahh/rzahn06.htm>

37

More Information



JDBC from RPG Enhancements

<http://systeminetwork.com/article/jdbc-rpg-enhancements>

- Includes links to other articles on MySQL, Oracle, DB2
- Includes sample RPG code
- Explains installation.

JDBC from RPG by Column Name

<http://systeminetwork.com/article/jdbc-rpg-column-name>

How to Handle Null Values in JDBC from RPG

<http://systeminetwork.com/article/handle-null-values-jdbc-rpg>

JDBC Escape Syntax

<http://db.apache.org/derby/docs/10.2/ref/rrefjdbc1020262.html>

Need Help? Try System iNetwork forums:

<http://forums.systeminetwork.com>

38

This Presentation



You can download a PDF copy of this presentation from:

<http://www.scottklement.com/presentations/>

Thank you!